

# Flashslide



Multi Format Reprographic Camera System  
Highly productive and professional

## Camera

- APS-C Sensor 24 Megapixel
- CMOS EXMOR 35 mm full frame sensor 36 MP
- CMOS EXMOR 35 mm full frame sensor 43 MP
- Up to 16 Bit color depth
- RAW and JPEG
- IR mode for dust and scratch removal
- Automatic white balance
- ARM processing unit
- Data transfer via USB
- HDMI connection, monitor required
- PC required

## Lenses:

- Canon Macro 65 mm

## Hardware:

- Reprographic table
- Combined touch screen and light table
- LED changeable cold light source 5000 K
- 110 – 240 V
- Size 80 x 50 x 30 cm / ca.16 kg

## Software :

- Remote camera control Ver.3.6  
Windows 7 - 8/8.1 – 10 and Mac 10.8-10.11
- Batch Processing
- Common image processing software such as  
SilverFast, Adobe CS, Capture One, HS ART etc.



APS 17 X 30 mm			
24 X 36 mm			
4,5 x 6 cm			
6 x 6 cm	6 x 7 cm	6 x 8 cm	6 x 9 cm



## Film Holders – Scanning Kits:

- APS-Film, 35 mm, 4,5 x 6 cm, 6 x 6 cm  
6 x 7 cm, 6 x 8 cm, 6 x 9 cm
- All other gates such as framed, single and film strip, Pocket 110,  
Minox, Agfa Rapid, Kodak Instamatic and Disc, Kodak 120, 127,  
129, 620, Zeiss Ikon Taxona, Fotothek films, etc.
- Roll and automatic feeds, slide magazine

